



# icListen

The new standard in broadband digital marine acoustics

The icListen Smart Hydrophone is the industry's most sensitive broadband digital hydrophone. It's a compact, all-in-one instrument capable of processing data while collecting in real-time.

Use icListen as a digital hydrophone, acoustic data logger, or both at once. Collect hard to detect data accurately and cost effectively while reducing data handling and storage.

## Introducing our new Smart Cable

**Smart Cable** - Connect four hydrophones to a single input connector. For more detail see Array Brochure.

Applications	HF	HF-X2	AF	AF(L)
Marine Mammal Monitoring	*		*	
Earthquake and Tsunamis				*
Pile Driving/Explosives		*		
Ocean Observatory	*		*	*
Pipeline Leak Detection	*			
Wind Farms	*			
Shipping Noise	*		*	

- **Detect** real-time events using Epoch Mode. Determine when spectral or WAV data is stored or transmitted in real-time.
- **Use** a web browser to access the webserver to setup, test, and operate icListen.
- **Synchronize** multiple hydrophones for a high quality multi-channel array avoiding the problem of cross-talk.
- **Simplify** data processing and project planning.
- **Wide** dynamic range eliminates gain settings.
- **Easy** to connect through a network, radio or cabled to a PC.
- **Compact** and self-contained, can be carried in one hand.
- **Extend** your reach beyond 100m using an Ethernet Repeater up to 500 m.




## icListen Models HF, AF



### 24-bit Smart Hydrophone

- Quiet
- Low Power
- Calibrated
- Acoustic Array
- High Value Rich Data
- Easy to Deploy



### Lucy Software

Lucy is used to setup and test icListen.

Display real-time waveform or waterfall displays using our PC software Lucy.

OceanSonics.com



**Bandwidth (+/- 6 dB)**

**HF:** 10 Hz to 200 kHz  
**AF(L):** 1 Hz to 12 kHz

**Sample Rate (Max S/sec)**

**HF:** 512,000 **HF-X2:** 512,000  
**AF(L):** 32,000

**Power**

24 Vdc input  
 2 W with Ethernet link

**Synchronization**

Accuracy 0.25 usec  
 Lock Range 1.0 Hz +/- 8 ppm  
 GPS PPS  
 External IEEE 1588 Module Optional

**Acquire Modes**

Record: Waveform / FFT / Epoch

**Maximum Internal Data Storage**

256 GB

**Dynamic Range**

**HF:** 95 dB  
**AF(L):** 106 dB

**Sensitivity**

**HF:** -169 dBV re.  $\mu$ Pa  
**HF-X2:** -209 dBV re.  $\mu$ Pa  
**AF(L):** -160 dBV re.  $\mu$ Pa

**Case Material and Depth**


Engineered Plastic and Titanium - 200m  
 Engineered Plastic and Titanium - 900m  
 Titanium - 3500m  
 Titanium - 6000m



Hill House  
 11 Lornevale Road, Great Village  
 Nova Scotia, Canada B0M 1L0  
 + 1 902 655 3000

# What makes icListen different?

The icListen replaces preamp, filters, converters and data link with a compact unit that gives trusted sound data in real units.



**Hydrophone Sensing Element;** ultra low noise and wide dynamic range for high signal quality and long term stability.

**Intelligent Digital Hydrophone** processes data before it is transmitted using spectral analysis and event detection, preconfigured for each application.

## Comparison of the icListen Models

icListen	Min Freq	Max Freq	Battery Life	Interface	Web Server	Self Noise
HF	10 Hz	200 kHz	10 Hours	Ethernet	Yes	27
HF(L)	1 Hz	200 kHz	10 Hours	Ethernet	Yes	27
HF-X2	1 Hz	200 kHz	10 Hours	Ethernet	Yes	67
AF	10 Hz	12 kHz	10 Hours	Ethernet	Yes	18
AF(L)	1 Hz	12 kHz	10 Hours	Ethernet	Yes	24

## Compare icListen Models to Ocean Ambient Levels

