



## NOTES:

- 1. FLOAT MATERIAL: SYNTACTIC FOAM, ABS COATED
- 2. BRIDLE MATERIAL: 316L STAINLESS STEEL
- 3. ROPE MATERIAL: POLYESTER, 700 kg SWL
- 4. MAX. WORKING DEPTH: 1500 m
- 5. MASS: 2.1 kg
- 6. BUOYANCY IN SEAWATER: 0.9 kg
- 7. BUOYANCY IN FRESH WATER: 0.8 kg

UNLESS OTHERWISE NOTED:

Ø187

1. DIMS IN MILLIMETRES 2. X  $\pm$  0.75 3. X.X  $\pm$  0.25

3. X.X ± 0.25 4. X.XX ± 0.075 5. ANGLES ± 1/2° 6. ECCENTRICITY 0.075 MAX 7. FLATNESS 0.075 T.I.R. 8. SURFACE FINISH: 125/



Ocean Sonics Limited

NOVA SCOTIA, CANADA

WWW.OCEANSONICS.COM

FLOAT COLLAR, 1500 m



SIZE Α

TITLE

DRAWING NUMBER

PUB-FC15

REV SCALE Α

SHEET 1:3 1 OF 1

THE INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND SHALL NOT BE MADE PUBLIC, OR COPIED, OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS UNLESS SPECIFICALLY AUTHORIZED IN WRITING BY OCEAN SONICS LIMITED. THIS DOCUMENT IS THE PROPERTY OF OCEAN SONICS LIMITED AND IS SUBJECT TO RETURN ON DEMAND. ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

COPYRIGHT © 2017 OCEAN SONICS LTD.